

SERIES: P12

Dial: 1½", 2", 2½", 4"
Accuracy: 1.6%, 2.5%

DESCRIPTION

Indumart *P12 Series* Standard Pressure Gauges with stainless steel casing and element are general purpose gauges suitable for a broad range of commercial and industrial applications. These dry gauges are used where liquid or gaseous media are not highly viscous and do not attack 316 stainless steel.

Due to their durability, Indumart *P12 Series* pressure gauges withstand difficult applications and thus are distinguished among all commercial pressure gauges available in the market.



SPECIFICATIONS

Accuracy	2.5% for 1½" & 2" dials; 1.6% for 2½" & 4" dials;
Dial Sizes	1½" (40 mm), 2" (50 mm), 2½" (63 mm), 4" (100 mm),
Case	304 Stainless Steel
Bezel	Push on ring for 1½", 2" & 2½" dials; Ring with screws for 4" dial
Window	Glass
Connection	Back, bottom
Thread	⅛" NPT (1½" dial only), ¼" NPT (2", 2½" dials) ½" NPT (4" dial) ¼" NPT (option for 1½" & 4" dials); BSP thread also available
Socket	SS304
Bourdon Tube	SS316
Max. Temperature	60°C
Range	0...10 to 0...8000 psi; 0...60 to 0...60000 kPa; 0...0.6 to 0...600 bar Vacuum and compound ranges are available; see the Range Table

ORDER CODES

Model P12

CONNECTION

Back
Bottom

K
T

DIAL SIZE

40 mm (1½")
50 mm (2")
63 mm (2½")
100 mm (4")

0
1
2
4

OPTIONS (more than one option may be selected)

¼" Process Connection (1½" and 4" dials only)
BSP Thread

NR
TB

Example: P12T4-NR, TB

Specifications may change without prior notice.