INDUMART Canada
www.indumart.com

Welding Pressure Gauges

SERIES: P15

Dial: 1½", 2", 2½"
Accuracy: 2.5%

DESCRIPTION

Indumart *P15 Series* Welding Pressure Gauges are applied for welding, cutting and related processes. They are mounted on oxygen or acetylene cylinders or on welding regulators to indicate the gas pressure. Because of the nature of their applications, these gauges meet maximum safety requirements.

Optionally, the *P15 Series* may be ordered with ABS casing.

SPECIFICATIONS

Accuracy	2.5%
Dial Sizes	1½" (40 mm), 2" (50 mm), 2½" (63 mm)
Case	Blue or yellow coloured Steel (std.), ABS (option)
Connection	Bottom
Thread	⅛" NPT (1½" dial), ¼" NPT (2", 2½" dials) BSP thread (option)
Window	Push-on plexiglass
Measuring Element	Bourdon or helical tube; Brass
Range	0...10 to 0...8000 psi; 0...60 to 0...60000 kPa; 0...0.6 to 0...600 bar See the Range Table

ORDER CODES

Model P15 [ ] [ ] [ ] — [ ]

CONNECTION
Bottom: T

DIAL SIZE
40 mm (1½"): 0
50 mm (2"): 1
63 mm (2½"): 2

APPLICATION
Acetylene Service: A
Oxygen Service: X

OPTIONS (more than one option may be selected)
ABS Case: CP
BSP Thread: TB

Example: P15T2X-CP,TB

Specifications may change without prior notice.